Sectioning commands with critical notes

This file provides examples of using sectioning command with reledmac. The section titles are in the line numbering, and have critical and side notes.

We use the `\reledxxx` commands, each of them in their own `\pstart. . . \pend` group.

Page breaks are manually added before chapter with `\beforeeledchapter`.

Chapter 1

chapter

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten..

1.1 section

1.1.1 subsection

subsubsection

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten.

1.2 section

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten.

---

1 chapter] chapitre
6 subsection] sous-section
7 subsubsection] sous-sous-section

Chapter 2

chapter

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten..

2.1 section

2.1.1 subsection

subsubsection

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten.

2.2 section

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten.

---

15 chapter] chapitre
20 subsection] sous-section
21 subsubsection] sous-sous-section